



CERT

DIN-DVGW type examination certificate

DIN-DVGW-Baumusterprüfzertifikat

NG-5126AU0320
Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of gas supply <i>Produkte der Gasversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	WILLBRANDT KG Schnackenburgallee 180, D-22525 Hamburg (Eidelstedt)
Distributor <i>Vertreiber</i>	WILLBRANDT KG Reinhold-Schleese-Straße 22, D-30179 Hannover
Product Category <i>Produktart</i>	greasing and sealing materials: Sealing material and HTB resistant seals for the gas installation (5117)
Product Description <i>Produktbezeichnung</i>	flat sealing material on synthetic fiber basis with higher thermal resistance
Model <i>Modell</i>	GASFALIT, DVGW, KTW, HTB
Test Reports <i>Prüfberichte</i>	type testing: 14/115/5126/1 from 10.10.2014 (EBI) laboratory control test: 22-00219-KP01 from 31.05.2022 (EBI)
Test Basis <i>Prüfgrundlagen</i>	DIN 30653 (01.08.2018)

Date of Expiry / File No. 30.06.2027 / 22-0373-GNV
Ablaufdatum / Aktenzeichen

04.08.2022 Fi A-1/2
Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle



DVGW CERT GmbH
Zertifizierungsstelle
Josef-Wirmer-Str. 1-3
53123 Bonn
Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993
www.dvgw-cert.com
info@dvgw-cert.com

Type	Technical Data	Remarks
Typ	Technische Daten	Bemerkungen
GASFALIT, DVGW, KTW, HTB, VP 401	pressure range: 1...5 bar	depending on the application

certified Components

zertifizierte Bauteile / Werkstoffe

Registr. No.	Component	Model/Type	Manufacturer
Registrier-Nr.	Bauteil (Produktart)	Modell/Typ	Hersteller
NG-5123BP0248	Flat sealing materials on synthetic fiber basis	novapress® BASIC/novapress® BASIC	Frenzelit GmbH
NG-5123BP0349	Flat sealing materials on synthetic fiber basis	GASFALIT/GASFALIT	WILLBRANDT KG

Hints of Utilization / Remarks

Verwendungshinweise / Bemerkungen

Field of application for pressure range ≤ 1 bar: gas meters with two-pipe- and one-pipe-screw connections according to DIN 3376-1, DIN 3376-2 or with flange connections according to DIN 3376-2

Field of application for pressure range ≤ 5 bar: pressure regulators with screw connections according to DIN 2993, DIN 3376-1, DIN 3376-2 and DIN EN 10242 as well as pressure regulators and tuning piston gas meters with flange connections according to DIN 2543, DIN 2633, DIN 3376-2, DIN EN 1092-1 and DIN EN 1092-2